

use and video conferencing.

The non-proprietary nature lets you interact your way in lecture halls, teacher training, campus technology initiatives or administrative meetings. Built-in cameras and microphones let you communicate with experts around the world, hassle-free, to broaden your students' horizons or push the boundaries for remote learning programs.

With a vivid 4K resolution on an optically bonded screen, the X Series provides a superior image quality that brings your lessons to life in stunning clarity. Optical bonding gives you an ultra-wide 178° viewing angle. No matter where your students sit, they can see the screen clearly.

Explore distance learning, communicate with experts, or host an internal training on a display with best-in-class image quality and our unique optical bonding technology. The only all-in-one collaboration solution for your educational needs.



Model	X5	Х6	X8	Х9
Display				
Screen Size	55"	65"	75"	86"
Display Area	47.62 x 26.79 in	56.23 x 31.63 in	64.97 x 36.55 in	74.69 x 42.05 in
Backlight	LED	LED	LED	LED
esolution	3840 x 2160 pixels	3840 x 2160 pixels	3840 x 2160 pixels	3840 x 2160 pixels
				16:9
Display Ratio	16:9	16:9	16:9	
rightness	370nit	370nit	370nit	370nit
iewi <mark>ng An</mark> gle	178°	178°	178°	178°
ifetime Hours	50,000 hours	50,000 hours	50,000 hours	50,000 hours
peakers, Cameras, Microphones	;			
peaker Position	Forward	Forward	Forward	Forward
peaker Frequency Response	65Hz - 12.5KHz	6.5Hz - 12.5KHz	6.5Hz - <mark>12.5KHz</mark>	6.5Hz - 12.5KHz
ax Power Output	(2) 15W	(2) 15W	(2) 15W	(2) 15W
icrophone Sensitivity	-38dBV±3dB	-38dBV±3dB	-38dBV±3dB	-38dBV±3dB
lic Fr <mark>eque</mark> ncy Response	65Hz - 12.5KHz	65Hz - 12.5KHz	65Hz - 12.5KHz	65Hz - 12.5KHz
lic Polar Patterns	Omni-directional	Omni-directional	Omni-directional	Omni-directional
lic Pickup Range	26.25 ft	26.25 ft	26.25 ft	26.25 ft
ic Quantity	4-element array	4-element array	4-element array	4-element array
amera Position	1 Top, 1 Bottom	1 Top, 1 Bottom	1 Top, 1 Bottom	1 Top, 1 Bottom
amera Sensor	2M Pixels	2M Pixels	2M Pixels	2M Pixels
amera Lens	86°	86°	86°	86°
ideo Resolution	1920x1080@30fps (Max)	1920x1080@30fps (Max)	1920x1080@30fps (Max)	1920x1080@30fps (Max)
ame Rate	30fps/60fps	30fps/60fps	30fps/60fps	30fps/60fps
ower	<100M/Chandby <0.5M/	220M (Chandhu 40 FM)	<200W (Chandby <0.5W)	≤450W (Standby ≤0.5W)
Max Power Consumption	≤180W (Standby ≤0.5W)	≤2 <mark>20W</mark> (Standby ≤0.5W)	≤300W (Standby ≤0.5W)	
Vorking Voltage	AC 100-240V, 50/60Hz	AC 100-240V, 50/60Hz	AC 100-240V, 50/60Hz	AC 100-240V, 50/60Hz
ouch				
ouch Surface	Anti-glare tempered glass	Optically bonded anti-glare glass	Optically bonded anti-glare glass	Optically bonded anti-glare glas
ouch Technology	InGlass™	InGlass™	InGlass™	InGlass™
ouch Points	Up to 20 Points	Up to 20 Points	Up to 20 Points	Up to 20 Points
/riting Tools	Stylus or Finger	Stylus or Fi <mark>nge</mark> r	Stylus or Finger	Stylus or Finger
ommunication Interface	USB-A	USB-A	USB-A	USB-A
ransportation/Storage				
	4495 42295 / 4007 0007 554	14°F - 122°F / 10% - 90% D51	14°F - 122°F / 10% - 90% D51	14°F - 122°F / 10% - 90% D51
torage Temperature/Humidity	14°F - 122°F / 10% - 90% D51		,	
	,	· ·	32°F - 104°F / 10% - 90%	32°F - 104°F / 10% - 90%
orking Temperature/Humidity	32°F - 104°F / 10% - 90%	32°F - 104°F / 10% - 90%	32°F - 104°F / 10% - 90%	32°F - 104°F / 10% - 90%
Jorking Temperature/Humidity	32°F - 104°F / 10% - 90% Wall-mount or Mobile Stand	32°F - 104°F / 10% - 90% Wall-mount or Mobile Stand	Wall-mount or Mobile Stand	Wall-mount or Mobile Stand
forking Temperature/Humidity lounting Options utline Dimension	32°F - 104°F / 10% - 90% Wall-mount or Mobile Stand 52 x 34.9 x 3.4 in	32°F - 104°F / 10% - 90% Wall-mount or Mobile Stand 61.7 x 41.1 x 3.5 in	Wall-mount or Mobile Stand 70.6 x 46.1 x 4 in	Wall-mount or Mobile Stand 80.3 x 51.8 x 4 in
Vorking Temperature/Humidity Mounting Options Putline Dimension	32°F - 104°F / 10% - 90% Wall-mount or Mobile Stand	32°F - 104°F / 10% - 90% Wall-mount or Mobile Stand	Wall-mount or Mobile Stand	Wall-mount or Mobile Stand
Vorking Temperature/Humidity Nounting Options Outline Dimension Veight Orts	32°F - 104°F / 10% - 90% Wall-mount or Mobile Stand 52 x 34.9 x 3.4 in 79.4 lbs	32°F - 104°F / 10% - 90% Wall-mount or Mobile Stand 61.7 x 41.1 x 3.5 in 99.2 lbs	Wall-mount or Mobile Stand 70.6 x 46.1 x 4 in 121.3 lbs	Wall-mount or Mobile Stand 80.3 x 51.8 x 4 in 174.10 lbs
Vorking Temperature/Humidity Iounting Options Putline Dimension Veight	32°F - 104°F / 10% - 90% Wall-mount or Mobile Stand 52 x 34.9 x 3.4 in 79.4 lbs	32°F - 104°F / 10% - 90% Wall-mount or Mobile Stand 61.7 x 41.1 x 3.5 in 99.2 lbs .4 (4K@30Hz) x 1, USB(Touch) x 1 U	Wall-mount or Mobile Stand 70.6 x 46.1 x 4 in 121.3 lbs ISB(Dynamic) x 2, Microphone In (Wall-mount or Mobile Stand 80.3 x 51.8 x 4 in 174.10 lbs 3.5mm) x 1
Vorking Temperature/Humidity Mounting Options Putline Dimension Veight Oorts Tront Interface Ports	32°F - 104°F / 10% - 90% Wall-mount or Mobile Stand 52 x 34.9 x 3.4 in 79.4 lbs	32°F - 104°F / 10% - 90% Wall-mount or Mobile Stand 61.7 x 41.1 x 3.5 in 99.2 lbs	Wall-mount or Mobile Stand 70.6 x 46.1 x 4 in 121.3 lbs ISB(Dynamic) x 2, Microphone In (Wall-mount or Mobile Stand 80.3 x 51.8 x 4 in 174.10 lbs 3.5mm) x 1
Vorking Temperature/Humidity Mounting Options Outline Dimension Veight Forts Front Interface Ports Inputs	32°F - 104°F / 10% - 90% Wall-mount or Mobile Stand 52 x 34.9 x 3.4 in 79.4 lbs	32°F - 104°F / 10% - 90% Wall-mount or Mobile Stand 61.7 x 41.1 x 3.5 in 99.2 lbs .4 (4K@30Hz) x 1, USB(Touch) x 1 U 4K@60Hz) x 2, HDMI (4K@30Hz) x 1	Wall-mount or Mobile Stand 70.6 x 46.1 x 4 in 121.3 lbs ISB(Dynamic) x 2, Microphone In (Wall-mount or Mobile Stand 80.3 x 51.8 x 4 in 174.10 lbs 3.5mm) x 1
Vorking Temperature/Humidity flounting Options dutline Dimension Veight orts ront Interface Ports aputs dutputs	32°F - 104°F / 10% - 90% Wall-mount or Mobile Stand 52 x 34.9 x 3.4 in 79.4 lbs HDMI 1 HDMI (4)	32°F - 104°F / 10% - 90% Wall-mount or Mobile Stand 61.7 x 41.1 x 3.5 in 99.2 lbs .4 (4K@30Hz) x 1, USB(Touch) x 1 U 4K@60Hz) x 2, HDMI (4K@30Hz) x 1	Wall-mount or Mobile Stand 70.6 x 46.1 x 4 in 121.3 lbs ISB(Dynamic) x 2, Microphone In (, DisplayPort (4K@60Hz) x 1, USB	Wall-mount or Mobile Stand 80.3 x 51.8 x 4 in 174.10 lbs 3.5mm) x 1 s(touch) x 4
Vorking Temperature/Humidity Itounting Options Outline Dimension Veight Orts Front Interface Ports Outputs Outputs Outputs	32°F - 104°F / 10% - 90% Wall-mount or Mobile Stand 52 x 34.9 x 3.4 in 79.4 lbs HDMI 1 HDMI (4)	32°F - 104°F / 10% - 90% Wall-mount or Mobile Stand 61.7 x 41.1 x 3.5 in 99.2 lbs .4 (4K@30Hz) x 1, USB(Touch) x 1 U 4K@60Hz) x 2, HDMI (4K@30Hz) x 1 HDMI Out (4K@60Hz) x 1, Line	Wall-mount or Mobile Stand 70.6 x 46.1 x 4 in 121.3 lbs ISB(Dynamic) x 2, Microphone In (, DisplayPort (4K@60Hz) x 1, USB	Wall-mount or Mobile Stand 80.3 x 51.8 x 4 in 174.10 lbs 3.5mm) x 1 s(touch) x 4
Vorking Temperature/Humidity Nounting Options Outline Dimension Veight Orts Tront Interface Ports Apputs Outputs Out	32°F - 104°F / 10% - 90% Wall-mount or Mobile Stand 52 x 34.9 x 3.4 in 79.4 lbs HDMI 1 HDMI (4)	32°F - 104°F / 10% - 90% Wall-mount or Mobile Stand 61.7 x 41.1 x 3.5 in 99.2 lbs .4 (4K@30Hz) x 1, USB(Touch) x 1 U 4K@60Hz) x 2, HDMI (4K@30Hz) x 1 HDMI Out (4K@60Hz) x 1, Line	Wall-mount or Mobile Stand 70.6 x 46.1 x 4 in 121.3 lbs ISB(Dynamic) x 2, Microphone In (, DisplayPort (4K@60Hz) x 1, USB	Wall-mount or Mobile Stand 80.3 x 51.8 x 4 in 174.10 lbs 3.5mm) x 1 s(touch) x 4
Vorking Temperature/Humidity Mounting Options Dutline Dimension Veight Orts ront Interface Ports Dutputs Dutputs Dither Other Major Features mbedded Operating System	32°F - 104°F / 10% - 90% Wall-mount or Mobile Stand 52 x 34.9 x 3.4 in 79.4 lbs HDMI 1 HDMI (USB(3.0) x 1,	32°F - 104°F / 10% - 90% Wall-mount or Mobile Stand 61.7 x 41.1 x 3.5 in 99.2 lbs .4 (4K@30Hz) x 1, USB(Touch) x 1 U 4K@60Hz) x 2, HDMI (4K@30Hz) x 1 HDMI Out (4K@60Hz) x 1, Line USB(2.0) x 2, RS232 x 1, RJ45 x 2, O Android	Wall-mount or Mobile Stand 70.6 x 46.1 x 4 in 121.3 lbs ISB(Dynamic) x 2, Microphone In (, DisplayPort (4K@60Hz) x 1, USB PORT (3.5mm) x 1, SPDIF Out x 1 PORT Slots (4K@60Hz) x 1, Power (E	Wall-mount or Mobile Stand 80.3 x 51.8 x 4 in 174.10 lbs 3.5mm) x 1 (touch) x 4
torage Temperature/Humidity Vorking Temperature/Humidity Mounting Options Outline Dimension Veight Forts Front Interface Ports Fron	32°F - 104°F / 10% - 90% Wall-mount or Mobile Stand 52 x 34.9 x 3.4 in 79.4 lbs HDMI 1 HDMI (4) USB(3.0) x 1,	32°F - 104°F / 10% - 90% Wall-mount or Mobile Stand 61.7 x 41.1 x 3.5 in 99.2 lbs .4 (4K@30Hz) x 1, USB(Touch) x 1 U 4K@60Hz) x 2, HDMI (4K@30Hz) x 1 HDMI Out (4K@60Hz) x 1, Line USB(2.0) x 2, RS232 x 1, RJ45 x 2, O	Wall-mount or Mobile Stand 70.6 x 46.1 x 4 in 121.3 lbs ISB(Dynamic) x 2, Microphone In (, DisplayPort (4K@60Hz) x 1, USB Out (3.5mm) x 1, SPDIF Out x 1 ISPS Slots (4K@60Hz) x 1, Power (E	Wall-mount or Mobile Stand 80.3 x 51.8 x 4 in 174.10 lbs 3.5mm) x 1 (touch) x 4 OC 5V-2A) Out x 1 Android



Toll-Free: 888-233-0868 Local: 972-468-9728

sales@newline-interactive.com www.newline-interactive.com